



Kabelleit- und Ablaufbock, verzinkt

Der Einsatz erfolgt unmittelbar hinter der Kabeltrommel.

Traglast: 200 kg

Gewicht: 15 kg

Bestell-Nr. 009.409.00

Cable guide and run-off frame, galvanized

This device is placed just behind the cable drum.

Carrying load: 200 kg

Weight: 15 kg

Order No. 009.409.00

Verstärkte Ausführung

zum Verlegen von schweren Kabeln und Rohren $\varnothing > 300$ mm

Traglast: 500 kg

Gewicht: 20 kg

Bestell-Nr. 009.409.10

Reinforced version

for laying of heavy cable and tube dia. > 300 mm

Carrying load: 500 kg

Weight: 20 kg

Order No. 009.409.10



Abrollschienen mit Arretierstange

Schienenabstand universell auf verschiedene

Kabeltrommelbreiten einstellbar;

Sicherung der Trommel durch Rollenarretierung

Reeling rails with fixing bar

Distance between rails is adjustable to different cable drum widths.

Securing of the drum by locking of rollers.

Bestell-Nr. Order No.	Max. Trommel- \varnothing Max. drum-dia. (mm)	Traglast Carrying load (kg)	Max. Trommelbreite Max. drum-width (mm)	Gewicht / Paar Weight / pair (kg)
009.676.00	1000	1000	800	31
009.676.10	1400	1500	900	33
009.676.20	1800	2000	1100	53
009.676.40	2800	2000	1650	86

Technische Änderungen vorbehalten. Specifications are subject to change without notice.